

# **BLANK PAGE**



# भारतीय मानक

आवृति नियंत्रण और चयन में प्रयुक्त क्वार्टज क्रिस्टल इकाइयां — विशिष्टि

भाग 5 दोलकों के लिये सी एक्स श्रेणी अनुमाग 15 क्वार्टज क्रिस्टल इकाई टाईप सी एक्स-15

Indian Standard

QUARTZ CRYSTAL UNITS
USED FOR FREQUENCY CONTROL
AND SELECTION—SPECIFICATION

PART 5 SERIES CX FOR OSCILLATORS

Section 15 Quartz Crystal Unit Type CX-15

UDC 621:373:5

@ BIS 1991

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002 Piezoelectric Devices for Frequency Control and Selection Sectional Committee, LTD 12

#### **FOREWORD**

This Indian Standard (Part 5/Sec 15) was adopted by the Bureau of Indian Standards on 17 May 1990, after the draft finalized by the Piezoelectric Devices for Frequency Control and Selection Sectional Committee had been approved by the Electronics and Telecommunication Division Council.

This standard shall be read in conjunction with IS 8271 (Part 1): 1981 'Specification for quartz crystal units used for frequency control and selection: Part 1 General requirements and tests (first revision)'.

This standard is based on JSS 50910 (1971) 'Detail specification for crystal unit, quartz, styles QC 36, QC 37, QC 38, QC 39, and QC 42' issued by the Directorate of Standardiztion, Ministry of Defence, India. The type of quartz crystal unit covered in this standard is equivalent to style QC 38 of JSS 50910 (1971).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

# Indian Standard

# QUARTZ CRYSTAL UNITS USED FOR FREQUENCY CONTROL AND SELECTION — SPECIFICATION

# PART 5 SERIES CX FOR OSCILLATORS

Section 15 Quartz Crystal Unit Type CX-15

#### 1 SCOPE

1.1 This standard (Part 5/Sec 15) Specifies detail requirements for the characteristics of quartz crystal unit Type CX-15 used for frequency control and selections in oscillators.

### 2 REFERENCES

2.1 The following Indian Standards have been referred to in this standard:

IS No.

Title

4570 ( Part 6 ): 1984

Specification for crystal unit holders: Part 6 Metal, solder seal, two-pin crystal unit

holder Type CX

8271 (Part 1): 1981 Specification for quartz crystal units used for frequency control and selection: Part 1 General requirements and tests (first revision)

# 3 OUTLINE AND DIMENSIONS

3.1 Holder outline shall conform to Type CX [ see IS 4570 ( Part 6 ): 1984 ].

# 4 MARKING

4.1 See 8 of IS 8271 (Part 1): 1981.

# 5 CONSTRUCTION AND WORKMANSHIP

5.1 See 7 of IS 8271 (Part 1): 1981.

# 6 TEST SCHEDULE AND DETAIL REQUIREMENTS

# 6.1 General Conditions for Test

See 9.2 of 1S 8271 (Part 1): 1981.

## 6.2 Test Schedule

The sequence and grouping of type, routine and acceptance tests shall be in accordance with 9.1 of IS 8271 (Part 1): 1981.

# 6.3 Detail Requirements

The detail requirements applicable to this particular type of crystal unit shall be as specified in Table 1.

# IS 8271 ( Part 5/Sec 15 ): 1990

Table 1 Detail Requirements of Quartz Crystal Unit Type CX 15

(Clause 6.3)

S1 Characteristics No.	Requirements
(1) (2)	(3)
a) Type of holder	CX ( See 3 )
b) Frequency range	50 to 125 MHz
c) Frequency tolerance;	
Operating temperature range	$\pm$ 50 ppm
d) Load capacitance	Infinity
e) Mode of oscillation	Fifth mechanical overtone
f) Operating temperature range	- 55°C to + 105°C
g) Test set, Calibration value & rated drive level	See Table 2
h) Capacitance shunt	7 pF, Max
j) Resonance resistance:	1,
i) 50 to 90 MHz	50 ohms, Max
ii) $90 + to 125 MHz$	60 ohms, Max
k) Shock [ as per <b>9.15</b> ( Severity A ) of IS 8271 ( Part 1 ) : 1981 ]:	
i) Frequency change permitted	$\pm$ 5 ppm
ii) Resonance resistance change permitted	± 10 percent
m) Vibration [ as per <b>9.16.1</b> ( Severity A ) of IS 8271 ( Part 1 ) 1981 ]:	
i) Frequency change permitted	$\pm$ 5 ppm
ii) Resonance resistance change permitted	± 10 percent
n) Temperature cycling:	
i) Frequency change permitted	$\pm$ 5 ppm
ii) Resonance resistance change permitted	± 10 percent
p) Ageing:	
Frequency change permitted	$\pm$ 5 ppm

Table 2 Test Set, Calibration Values and Rated Drive Level

[ Table 1 (g)]

Frequency Range	Calibration		Rated	Test
Nange	Resistance	Resistor voltage	Drive Level	Set
MHz	ohms	volt	${f mW}$	
(1)	(2)	(3)	(4)	(5) :
Up to 100	60	0.32	$2.0 \pm 0.4$	TS-68 <b>3</b> /TSM
Above 100	60	0.35	$2.0 \pm 0.4$	AN/TSM-15

#### Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

#### Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

#### Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. LTD 12 (1399)

Amendments	lasved Since	Publication
------------	--------------	-------------

STREET STREET STREET STREET			
Amend No.	Date of Issue	Text Affecte	

### BUREAU OF INDIAN STANDARDS

#### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Terephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha (Common to all Offices)

### Regional Offices:

Central: Manak Bhavan, 9 Bahadur Shah	n Zafar Marg	∫331 01 31
NEW DELHI 110002		<b>\ \ 331 13 75</b>

Eastern: 1/14 C.I.T. Scheme VII M, V.I.P. Road, Maniktola
CALCUTTA 700054

37 86 62

Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036 2 18 43

Southern: C.I.T. Campus, IV Cross Road, MADRAS 600113 41 29 16

Western: Manakalaya, E9 MIDC, Marol, Andheri (East) 6 32 92 95

BOMBAY 400093

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.

COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI.

HYDERABAD. JAIPUR. KANPUR. PATNA. THIRUVANANTHAPURAM.